

Rubber Protection Cover
for Fire Extinguishing Generators of type: Dymameco 2000-E02/E03
Type: Dymameco GSA 2000

Technical Data:

Height (with Dymameco 2000-E02/E03 assembly):	approx. 370 mm
Diameter:	approx. 217 mm
Bellows material:	42 CR 764
Weight: (with hose clamps)	approx. 0.45 kg
Cable gland:	polyamide, metric M12 x 1.5
Protection class:	IP 67
Temperature range:	-40°C to 100°C
PN:	80564



Important: A cable loop of approx. 20 cm must be set into the space between the rubber protection cover and fire extinguishing generator, after connecting the squib connector to the fire extinguishing generator, before the final mounting of the rubber protection cover, so thus the squib connector can't be damaged during operation and during disassembly!

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date	02/25/2020
Version	4

EGON HARIG GmbH
 Gewerbering 4 • D-22113 Oststeinbek
 Tel./Phone: +49 (0)40 713752-0
 Telefax: +49 (0)40 713752-24
 E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No.	4.11003.1-1
Page 1 of 1	