

AEROSOL Fire Extinguishing Generator (with thermal activator) Type: Dynameco 300-TA08

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.



standard version



optional version

Characteristics:

- Manufacturer: Dynamit Nobel Defence
 - P/N: 40 205
 - Volume to be protected: approx. 3 m³
 - Non-toxic extinguishing agent AEROSOL
 - Autarchic system: "stand-alone" because there no power supply and no control units for the ignition are required.
 - Standard versions* of thermal activators for activation temperatures: 57°C, 68°C, 79°C and 93°C (other temperature ranges on request)
 - **optional End-Position Switch**** (potential-free NC contact) **with HT connection cable (shielded)** (standard length: 2 m) available for the feedback of the "Released" state:
Type: Dynameco TA08-ES, P/N: 80 500
- * The activation temperature of the thermal activator must be already specified when ordering.
- ** The optional End-Position Switch, such as deviating cable length must be specified when ordering, too! Because the Fire Extinguishing Generator must be modified and the cable must be prepared by the factory for this functional extension.

Technical Data:

Without End-Position Switch as standard version:

Height	= approx. 259 mm
Diameter	= approx. 82 mm
Diameter _{max.}	= approx. 88 mm
Weight	= approx. 1.41 kg

With the End-Position Switch in compliance with the min. bend radius of the shielded connection cable:

Height with End-Position Switch and connection cable	= approx. 349 mm
Weight with End-Position Switch and connection cable	= approx. 1.48 kg
Connection cable:	AWG 20 (2 x 0.62 ²)
Ambient temperature range of the connection cable:	-40°C to +150°C

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date 09/28/2013

Version 0/W.HR

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Catalog sheet No
4.13262.1-1