

Connection Cable (shielded)
(for fire extinguishing generators of types: Dymameco 50-E03)
Type: Dymameco AK1 ...

Technical Data

Connection socket (squib connector)

Housing material:	PA
Contact material:	tin-coated copper, selective gold plated
Connection:	2-pole
Secure closure:	latching hook (self-locking)
EMC protection:	ferrite
Operating temperature range:	-40°C to +90°C

HT-connection cable

Cable type:	2-wire, twisted, shielded
Jacket color:	white
Conductor cross sections:	2 x 0.62 mm ² (AWG 20)
Conductor material:	tin-coated copper
Conductor types:	fine-wire
Outer diameter:	3.76 mm
EMC protection:	shielding braid
Operating temperature range:	-65°C to +150°C

Type-specific Data

Type: Dymameco AK1 25 Length: 2.5 m
P/N: 50 398

Type: Dymameco AK1 50 Length: 5 m
P/N: 50 402

Type: Dymameco AK1 100 Length: 10 m
P/N: 50 403

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date	02/25/2020
Version	1

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No	4.14011.1-1
Page 1 of 1	