

Control Panel
(Operator Panel)
Type: BED 1012 LU

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

1. Technical Data

Housing Dimensions (H x W x D): (w/o cable gland and w/o mountings)	185 mm x 80 mm x 78 mm
Housing material:	ABS (plastic)
Weight (without connection cable):	approx. 0.5 kg
Housing protection:	IP 54
Operating temperature range:	-10 °C to +60 °C
Cable gland:	polyamide, metric, M20 x 1.5 for cable diameters from 6 mm to 12 mm
Connection type for Central Units of types BMLZ 1012... :	connection cable, length 2,5 m (or by appointment) with color-coded wires and 0.5 mm ² wire-end ferrules.

2. Electrical Data

Input:

Nominal input voltage:	24 V DC ±20%
Nominal input currents on 24 V DC	
Ready for operation:	min. 0.05 A
Release:	max. 0.1 A

3. Labeling language

Standard:	German
or by appointment:	English, French, ...

4. Controls and indicators

Signaling elements:

“Operation”	LED green
“Alarm”	LED red
“Released”	LED red (integrated in “Manual Release” push button)

Control elements:

“Reset”	push button
“Automatic Release OFF/ON”	rotary switch
“Manual Release”	illuminated push button (covered and sealable)

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date

07/16/2014

Version

0/W.HR

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

4.14168.2-1

Page 1 of 1