

Rubber Protection Cover
(for fire extinguishing generators of types: Dynameco 50-E03)
Type: Dynameco GSA 50

Technical Data:

Height (with Dynameco 50-E03 assembly):	max. 240 mm
Diameter:	max. 72 mm
Bellows material:	42 CR 764
Weight (with hose clamps):	approx. 0.1 kg
Cable gland:	polyamide, metric M12 x 1.5
Protection class:	IP 67
Temperature range:	-40°C to 100°C
PN:	80 275



Important: A cable loop of approx. 10 cm must be set into the space of the rubber protection cover, after connecting the squib connector to the fire extinguishing generator, before the final mounting of the rubber protection cover, so thus the squib connector can't be damaged during operation and during disassembly!

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date

12/02/2014

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

4.14336-1

Version

0/W.HR

Page 1 of 1