

Type: **Dynameco AVLH**P/N: **80672****1 Technical Data**

Release device (incl. cable connection)

length/ width/ height:	approx. 622 mm / 323 mm / 428 mm
housing material:	V2A
weight (excl. fire ext. gen.):	approx. 48 kg
housing protection class:	IP30

Manual release push button

length/ width/ height:	152 mm / 80 mm / 88 mm
housing material:	aluminium
weight:	approx. 0.5 kg
housing protection class:	IP30

Operating temperature range: -20°C to +60°C

Cable, connection release device / manual release

Length / diameter:	approx. 10 m / 3G 0.75 mm ²
weight:	approx. 0.7 kg

Connector manual release: „X2“, type: socket C16-1, 4-pin

Connector release device: „X3“, type: plug C16-1, 4-pin

Release connector: „2E1“ – „2E6“, type: T&B L 3-02C, 2-pin

2 Electrical Data

Operating voltage (battery): 9.0 V DC

2.1 Current consumption (with 9.0 V DC)

Switching current: approx. 1.5 A

3 Paint finish:

Release device: untreated

Manual release: RAL 1003 (signal yellow)

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatsoever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Issue Date

1st of July 2018

Version

0

EGON HARIG GmbH
 Gewerbering 4 • D-22113 Oststeinbek
 Tel./Phone: +49 (0)40 713752-0
 Telefax: +49 (0)40 713752-24
 E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Data Sheet No.

4.18180.2

Page 1 of 1